

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Product form	: Mixture
Product name	: 360/A303 - BRILLIANT ALUMINIUM PAINT
UFI	: PQ2P-G22V-S00F-QURK
Product code	: 10662
Type of product	: Paint
Product group	: End product
Other means of identification	: 360/A303/3

1.2. Relevant identified uses of the substance or mixture and uses advised against**1.2.1. Relevant identified uses**

No additional information available

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet**Supplier**

Coo-Var
Lockwood Street
Hull – East Yorkshire
England
T +44 (0)1482 328053
info@coo-var.co.uk

Distributor

Teal & Mackrill EU B.V.
Queens Towers
Delflandlaan 1
1062 EA Amsterdam
Netherlands
T +31 (0)208 004828
info@teamac.co.uk

1.4. Emergency telephone number

Emergency number : +44 (0) 1482 328053 Coo-Var (08.30 - 16.30 hrs Mon - Thurs, 08.30 - 15.00 hrs Fri)

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Classification according to Regulation (EC) No. 1272/2008 [CLP]**

Flammable liquids, Category 3	H226
Specific target organ toxicity – Single exposure, Category 3, Narcosis	H336
Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation	H335
Aspiration hazard, Category 1	H304
Hazardous to the aquatic environment – Chronic Hazard, Category 2	H411
Full text of H- and EUH-statements: see section 16	

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements**Labelling according to Regulation (EC) No. 1272/2008 [CLP]**

Hazard pictograms (CLP) :



GHS02

GHS07

GHS08

GHS09

Signal word (CLP) :

: Danger

360/A303 - BRILLIANT ALUMINIUM PAINT

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Contains	: Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics; HYDROCARBONS, C9, AROMATICS
Hazard statements (CLP)	: H226 - Flammable liquid and vapour. H304 - May be fatal if swallowed and enters airways. H335 - May cause respiratory irritation. H336 - May cause drowsiness or dizziness. H411 - Toxic to aquatic life with long lasting effects.
Precautionary statements (CLP)	: P101 - If medical advice is needed, have product container or label at hand. P102 - Keep out of reach of children. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261 - Avoid breathing dust/fume/gas/mist/vapours/spray. P271 - Use only outdoors or in a well-ventilated area. P273 - Avoid release to the environment. P280 - Wear protective gloves/protective clothing/eye protection/face protection. P301+P330+P331 - IF SWALLOWED: rinse mouth. Do NOT induce vomiting. P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.
EUH-statements	: EUH066 - Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards

Contains no PBT/vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
HYDROCARBONS, C9, AROMATICS substance with national workplace exposure limit(s) (GB)	CAS-No.: 64742-95-6 EC-No.: 918-668-5 REACH-no: 01-2119455851-35	$\geq 10 - < 30$	Flam. Liq. 3, H226 STOT SE 3, H336 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	EC-No.: 919-857-5 REACH-no: 01-2119463258-33	$\geq 10 - < 30$	Flam. Liq. 3, H226 STOT SE 3, H336 Asp. Tox. 1, H304
Dipropylene Glycol Methyl Ether substance with national workplace exposure limit(s) (GB)	CAS-No.: 34590-94-8 EC-No.: 252-104-2 REACH-no: 01-2119450011-60	< 1	Not classified
2,6-Di-tert-butyl-p-cresol substance with national workplace exposure limit(s) (GB)	CAS-No.: 128-37-0 EC-No.: 204-881-4 REACH-no: 01-2119565113-46	< 1	Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Full text of H- and EUH-statements: see section 16

360/A303 - BRILLIANT ALUMINIUM PAINT

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Get medical advice/attention if you feel unwell.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse.
First-aid measures after eye contact	: Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing.
First-aid measures after ingestion	: Get immediate medical advice/attention. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

No additional information available

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: dry chemical powder, alcohol-resistant foam, carbon dioxide (CO ₂).
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Flammable liquid and vapour.
Hazardous decomposition products in case of fire	: Thermal decomposition generates : Carbon dioxide. Carbon monoxide. Toxic fumes may be released.

5.3. Advice for firefighters

Precautionary measures fire	: Keep container closed when not in use.
Firefighting instructions	: Use water spray or fog for cooling exposed containers.
Protection during firefighting	: Use self-contained breathing apparatus and chemically protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Do not handle until all safety precautions have been read and understood. Avoid contact with skin and eyes.
------------------	---

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Prevent liquid from entering sewers, watercourses, underground or low areas. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment	: Do not touch or walk on the spilled product. Cover spill with non combustible material, e.g.: sand, earth, vermiculite.
Methods for cleaning up	: Clean up any spills as soon as possible, using an absorbent material to collect it. Collect spillage. This material and its container must be disposed of in a safe way, and as per local legislation.

360/A303 - BRILLIANT ALUMINIUM PAINT

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection".

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Additional hazards when processed : The Manual Handling Operations Regulations may apply to the handling of containers of this product. To assist employers, the following method of calculating the weight for any pack size is given. Take the pack size volume in litres and multiply this figure by the specific gravity value given in section 9. This will give the net weight of the coating in kilograms. Allowance will then have to be made for the immediate packaging to give an approximate gross weight.
- Precautions for safe handling : Do not breathe vapours. Avoid contact with skin and eyes. Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : The storage and use of this product is subject to the Dangerous Substances and Explosive Atmospheres Regulations (DSEAR). The requirements are given in the HSE Approved Code of Practice and Guidance, Storage of Dangerous Substances: DSEAR. Up to 250 litres of liquids with a flashpoint above 32C but below 55C may be kept in a workroom provided they are kept in closed containers in a marked, fire-resisting cupboard or bin. Larger quantities must be kept in a separate, marked storeroom conforming to the structural requirements contained in the HSE guidance note Storage of Flammable Liquids in Containers.
- Storage conditions : Keep container tightly closed. Store in a dry place. Store in a closed container.
- Incompatible products : Oxidizing agent. Strong acids.
- Storage temperature : 5 – 25 °C

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

Dipropylene Glycol Methyl Ether (34590-94-8)	
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA) [1]	308 mg/m ³
WEL TWA (OEL TWA) [2]	50 ppm
HYDROCARBONS, C9, AROMATICS (64742-95-6)	
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA) [1]	19 mg/m ³ (8 hour)
WEL TWA (OEL TWA) [2]	100 ppm (8 hour)
2,6-Di-tert-butyl-p-cresol (128-37-0)	
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA) [1]	10 mg/m ³

8.1.2. Recommended monitoring procedures

No additional information available

360/A303 - BRILLIANT ALUMINIUM PAINT

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Provide local exhaust or general room ventilation.

8.2.2. Personal protection equipment

Personal protective equipment:

Protective goggles. Protective clothing. Wear protective gloves.

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Chemical goggles or safety glasses

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Protective gloves

8.2.2.3. Respiratory protection

No additional information available

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Do not exceed the occupational exposure limits (OEL).

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Silver.
Appearance	: Metallic. Viscous liquid.
Odour	: Not available
Odour threshold	: Not available
Melting point	: Not available
Freezing point	: Not available
Boiling point	: Not available
Flammability	: Not available
Explosive limits	: Not available
Lower explosion limit	: Not available
Upper explosion limit	: Not available

360/A303 - BRILLIANT ALUMINIUM PAINT

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Flash point	: 45 °C Closed cup.
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: Technically not feasible.
Viscosity, kinematic	: > 20.5 mm ² /s
Solubility	: insoluble in water.
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Density	: Not available
Relative density	: 0.97 – 1.01 @ 20°C
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions of use.

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

Oxidizing agent. Strong acids.

10.6. Hazardous decomposition products

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified
Skin corrosion/irritation	: Not classified
	pH: Technically not feasible.

HYDROCARBONS, C9, AROMATICS (64742-95-6)

pH	Not available.
----	----------------

Serious eye damage/irritation	: Not classified
	pH: Technically not feasible.

360/A303 - BRILLIANT ALUMINIUM PAINT

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

HYDROCARBONS, C9, AROMATICS (64742-95-6)

pH	Not available.
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: May cause drowsiness or dizziness. May cause respiratory irritation.

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

HYDROCARBONS, C9, AROMATICS (64742-95-6)

STOT-single exposure	May cause drowsiness or dizziness. May cause respiratory irritation.
STOT-repeated exposure	: Not classified
Aspiration hazard	: May be fatal if swallowed and enters airways.

360/A303 - BRILLIANT ALUMINIUM PAINT

Viscosity, kinematic	> 20.5 mm ² /s
----------------------	---------------------------

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

Viscosity, kinematic	≤ 20.5 mm ² /s
----------------------	---------------------------

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Toxic to aquatic life with long lasting effects.
Not rapidly degradable	
Additional information	: No data available.

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

Other adverse effects	: This product contains Volatile Organic Compounds (VOCs) which have a photochemical ozone creation potential.
-----------------------	--

360/A303 - BRILLIANT ALUMINIUM PAINT

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste)	: Disposal must be done according to official regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Product/Packaging disposal recommendations	: Avoid release to the environment.
European List of Waste (LoW) code	: 08 01 11* - waste paint and varnish containing organic solvents or other dangerous substances 15 01 02 - plastic packaging 15 01 04 - metallic packaging
HP Code	: HP3 - "Flammable:" – flammable liquid waste: liquid waste having a flash point below 60 °C or waste gas oil, diesel and light heating oils having a flash point > 55 °C and ≤ 75 °C; – flammable pyrophoric liquid and solid waste: solid or liquid waste which, even in small quantities, is liable to ignite within five minutes after coming into contact with air; – flammable solid waste: solid waste which is readily combustible or may cause or contribute to fire through friction; – flammable gaseous waste: gaseous waste which is flammable in air at 20 °C and a standard pressure of 101.3 kPa; – water reactive waste: waste which, in contact with water, emits flammable gases in dangerous quantities; – other flammable waste: flammable aerosols, flammable self-heating waste, flammable organic peroxides and flammable self-reactive waste. HP5 - "Specific Target Organ Toxicity (STOT)/Aspiration Toxicity:" waste which can cause specific target organ toxicity either from a single or repeated exposure, or which cause acute toxic effects following aspiration. HP14 - "Ecotoxic:" waste which presents or may present immediate or delayed risks for one or more sectors of the environment

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
UN 1263	UN 1263	UN 1263	UN 1263	UN 1263
14.2. UN proper shipping name				
PAINT	PAINT	Paint	PAINT	PAINT
Transport document description				
UN 1263 PAINT, 3, III, (D/E), ENVIRONMENTALLY HAZARDOUS	UN 1263 PAINT, 3, III, MARINE POLLUTANT/ENVIRONMENTALLY HAZARDOUS	UN 1263 Paint, 3, III, ENVIRONMENTALLY HAZARDOUS	UN 1263 PAINT, 3, III, ENVIRONMENTALLY HAZARDOUS	UN 1263 PAINT, 3, III, ENVIRONMENTALLY HAZARDOUS
14.3. Transport hazard class(es)				
3	3	3	3	3
14.4. Packing group				
III	III	III	III	III

360/A303 - BRILLIANT ALUMINIUM PAINT


Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ADR	IMDG	IATA	ADN	RID
14.5. Environmental hazards				
Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes
No supplementary information available				

14.6. Special precautions for user

Overland transport

Classification code (ADR)	: F1
Special provisions (ADR)	: 163, 367, 650
Limited quantities (ADR)	: 5I
Excepted quantities (ADR)	: E1
Packing instructions (ADR)	: P001, IBC03, LP01, R001
Special packing provisions (ADR)	: PP1
Mixed packing provisions (ADR)	: MP19
Portable tank and bulk container instructions (ADR)	: T2
Portable tank and bulk container special provisions (ADR)	: TP1, TP29
Tank code (ADR)	: LGBF
Vehicle for tank carriage	: FL
Transport category (ADR)	: 3
Special provisions for carriage - Packages (ADR)	: V12
Special provisions for carriage - Operation (ADR)	: S2
Hazard identification number (Kemler No.)	: 30
Orange plates	: 
Tunnel restriction code (ADR)	: D/E
EAC code	: •3Y

Transport by sea

Special provisions (IMDG)	: 163, 223, 367, 955
Limited quantities (IMDG)	: 5 L
Excepted quantities (IMDG)	: E1
Packing instructions (IMDG)	: P001, LP01
Special packing provisions (IMDG)	: PP1
IBC packing instructions (IMDG)	: IBC03
Tank instructions (IMDG)	: T2
Tank special provisions (IMDG)	: TP1, TP29
EmS-No. (Fire)	: F-E
EmS-No. (Spillage)	: S-E
Stowage category (IMDG)	: A
Properties and observations (IMDG)	: Miscibility with water depends upon the composition.

Air transport

PCA Excepted quantities (IATA)	: E1
PCA Limited quantities (IATA)	: Y344
PCA limited quantity max net quantity (IATA)	: 10L
PCA packing instructions (IATA)	: 355
PCA max net quantity (IATA)	: 60L
CAO packing instructions (IATA)	: 366
CAO max net quantity (IATA)	: 220L
Special provisions (IATA)	: A3, A72, A192
ERG code (IATA)	: 3L

Inland waterway transport

Classification code (ADN)	: F1
---------------------------	------

360/A303 - BRILLIANT ALUMINIUM PAINT

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Special provisions (ADN)	: 163, 367, 650
Limited quantities (ADN)	: 5 L
Excepted quantities (ADN)	: E1
Equipment required (ADN)	: PP, EX, A
Ventilation (ADN)	: VE01
Number of blue cones/lights (ADN)	: 0

Rail transport

Classification code (RID)	: F1
Special provisions (RID)	: 163, 367, 650
Limited quantities (RID)	: 5L
Excepted quantities (RID)	: E1
Packing instructions (RID)	: P001, IBC03, LP01, R001
Special packing provisions (RID)	: PP1
Mixed packing provisions (RID)	: MP19
Portable tank and bulk container instructions (RID)	: T2
Portable tank and bulk container special provisions (RID)	: TP1, TP29
Tank codes for RID tanks (RID)	: LGBF
Transport category (RID)	: 3
Special provisions for carriage – Packages (RID)	: W12
Colis express (express parcels) (RID)	: CE4
Hazard identification number (RID)	: 30

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Other information, restriction and prohibition regulations : Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 and all its amendments and modifications. Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 and all its amendments and modifications. Commission Regulation (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006.

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

Explosives Precursors Regulation (2019/1148)

Contains substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)
Please see https://ec.europa.eu/home-affairs/system/files/2021-11/list_of_competent_authorities_and_national_contact_points_en.pdf

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

360/A303 - BRILLIANT ALUMINIUM PAINT

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Abbreviations and acronyms:	
CAS-No.	Chemical Abstract Service number
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DNEL	Derived-No Effect Level
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
PBT	Persistent Bioaccumulative Toxic
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
SDS	Safety Data Sheet
VOC	Volatile Organic Compounds
vPvB	Very Persistent and Very Bioaccumulative

Full text of H- and EUH-statements:	
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
EUH066	Repeated exposure may cause skin dryness or cracking.
Flam. Liq. 3	Flammable liquids, Category 3
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis

The classification complies with : ATP 12

Safety Data Sheet (SDS), EU

360/A303 - BRILLIANT ALUMINIUM PAINT

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.