

SAFETY DATA SHEET

600/V607 - SWIMMING POOL PAINT THINNERS

According to Regulation (EC) No 1907/2006, Annex II, as amended. Commission Regulation (EU) No 2015/830 of 28 May 2015.

SECTION 1: Identification of t	he substance/mixture and of the company	y/undertaking
1.1. Product identifier		
Product name	600/V607 - SWIMMING POOL PAINT	THINNERS
Product number	600/V607/15SP	
UFI	UFI: 5DJP-123S-5003-U7DM	
1.2. Relevant identified uses of	of the substance or mixture and uses advi	sed against
Identified uses	Paint.	
1.3. Details of the supplier of t	the safety data sheet	
Supplier	COO-VAR Lockwood Street HULL UK HU2 0HN +441482328053 (T) +441482219266 (F) info@coo-var.co.uk	TEAL & MACKRILL EU B.V. Zandvoortstraat 69 1976 BN IJMUIDEN THE NETHERLANDS +441482328053 (T) +441482219266 (F) info@coo-var.co.uk
Contact person	Technical Department -, 08.30 - 16.30 I	nrs Mon - Thurs, 08.30 - 15.00 hrs Fri, as above
1.4. Emergency telephone nu	mber	
Emergency telephone	+44 (0) 1482 328053 Coo-Var (08.30 -	16.30 hrs Mon - Thurs, 08.30 - 15.00 hrs Fri)
SDS No.	21113	
SECTION 2: Hazards identific	ation	
2.1. Classification of the subst Classification (EC 1272/2008) Physical hazards		
Health hazards	·	
nealui nazalus	STOT SE 3 - H335, H336 Asp. Tox. 1 -	H304
Environmental hazards	· · ·	H304
	STOT SE 3 - H335, H336 Asp. Tox. 1 - Aquatic Chronic 2 - H411	H304

Hazard statements	H226 Flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H411 Toxic to aquatic life with long lasting effects.
Precautionary statements	 P102 Keep out of reach of children. P101 If medical advice is needed, have product container or label at hand. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261 Avoid breathing vapour/ spray. P271 Use only outdoors or in a well-ventilated area. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor. P331 Do NOT induce vomiting. P501 Dispose of contents/ container in accordance with national regulations.
Supplemental label information	EUH066 Repeated exposure may cause skin dryness or cracking.
Contains	Hydrocarbons, C9, aromatics
Supplementary precautionary statements	P403+P233 Store in a well-ventilated place. Keep container tightly closed.

2.3. Other hazards

This substance is not classified as PBT or vPvB according to current EU criteria.

SECTION 3: Composition/information on ingredients

3.2. Mixtures		
HYDROCARBONS, C9, AROMATICS		60-100%
CAS number: —	EC number: 918-668-5	REACH registration number: 01- 2119455851-35-xxxx
Classification	Classificatio	on (67/548/EEC or 1999/45/EC)
Flam. Liq. 3 - H226	Xn;R65. Xi;	R37. N;R51/53. R10,R66,R67.
STOT SE 3 - H335, H336		
Asp. Tox. 1 - H304		
Aquatic Chronic 2 - H411		

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	Get medical attention if any discomfort continues. Show this Safety Data Sheet to the medical personnel.
Inhalation	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Maintain an open airway. Loosen tight clothing such as collar, tie or belt.
Ingestion	Rinse mouth thoroughly with water. Remove any dentures. Give a few small glasses of water or milk to drink. Stop if the affected person feels sick as vomiting may be dangerous. Do not induce vomiting unless under the direction of medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. Maintain an open airway. Loosen tight clothing such as collar, tie or belt.

Skin contact	Remove affected person from source of contamination. Rinse immediately with plenty of water.
Eye contact	Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 10 minutes.
Protection of first aiders	First aid personnel should wear appropriate protective equipment during any rescue.
4.2. Most important symptoms	and effects, both acute and delayed
General information	See Section 11 for additional information on health hazards. The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Inhalation	Prolonged inhalation of high concentrations may damage respiratory system. During application and drying, solvent vapours will be emitted. Vapours in high concentrations are narcotic.
Ingestion	Gastrointestinal symptoms, including upset stomach. Fumes from the stomach contents may be inhaled, resulting in the same symptoms as inhalation.
Skin contact	Prolonged contact may cause dryness of the skin. Discoloration of the skin.
Eye contact	May cause temporary eye irritation.
4.3. Indication of any immedia	te medical attention and special treatment needed
Notes for the doctor	Treat symptomatically.
Specific treatments	No special treatment required.
SECTION 5: Firefighting meas	sures
5.1. Extinguishing media	
Suitable extinguishing media	The product is flammable. Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Use fire-extinguishing media suitable for the surrounding fire.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
5.2. Special hazards arising fr	om the substance or mixture
Specific hazards	Containers can burst violently or explode when heated, due to excessive pressure build-up. Flammable liquid and vapour. Vapours may be ignited by a spark, a hot surface or an ember. Vapours may form explosive mixtures with air. Fire-water run-off in sewers may create fire or explosion hazard.
Hazardous combustion products	Thermal decomposition or combustion products may include the following substances: Harmful gases or vapours.
5.3. Advice for firefighters	
Protective actions during firefighting	Avoid breathing fire gases or vapours. Evacuate area. Keep upwind to avoid inhalation of gases, vapours, fumes and smoke. Ventilate closed spaces before entering them. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapours and protect men stopping the leak. Avoid discharge to the aquatic environment. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities.
Special protective equipment for firefighters	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing conforming to European standard EN469 (including helmets, protective boots and gloves) will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions No action shall be taken without appropriate training or involving any personal risk. Keep unnecessary and unprotected personnel away from the spillage. Wear protective clothing as described in Section 8 of this safety data sheet. Follow precautions for safe handling described in this safety data sheet. Wash thoroughly after dealing with a spillage. Provide adequate ventilation.

6.2. Environmental precautions

Environmental precautions Avoid discharge to the aquatic environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning upWear protective clothing as described in Section 8 of this safety data sheet. Clear up spills
immediately and dispose of waste safely. Reuse or recycle products wherever possible.
Absorb spillage to prevent material damage. Flush contaminated area with plenty of water.
Wash thoroughly after dealing with a spillage. Dispose of contents/container in accordance
with national regulations.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. For waste disposal, see Section 13.

SECTION 7: Handling and storage 7.1. Precautions for safe handling Usage precautions Read and follow manufacturer's recommendations. Wear protective clothing as described in

SECTION 8: Exposure controls/Personal protection		
Usage description	Take precautionary measures against static discharges.	
Specific end use(s)	The identified uses for this product are detailed in Section 1.2.	
7.3. Specific end use(s)		
Storage class	Unspecified storage.	
Storage precautions	Store away from incompatible materials (see Section 10). No specific recommendations.	
7.2. Conditions for safe sto	orage, including any incompatibilities	
Advice on general occupational hygiene	Wash promptly if skin becomes contaminated. Take off contaminated clothing. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Wash at the end of each work shift and before eating, smoking and using the toilet. Change work clothing daily before leaving workplace.	
Usage precautions	Section 8 of this safety data sheet. Keep away from food, drink and animal feeding stuffs. Handle all packages and containers carefully to minimise spills. Keep container tightly sealed when not in use. Avoid the formation of mists.	

8.1. Control parameters

Occupational exposure limits

HYDROCARBONS, C9, AROMATICS

Long-term exposure limit (8-hour TWA): WEL 19 ppm 100 mg/m³ vapour WEL = Workplace Exposure Limit.

DNEL	Consumer - Oral; Long term systemic effects: 11 mg/kg/day Consumer - Dermal; Long term systemic effects: 11 mg/kg/day Consumer - Inhalation; Long term systemic effects: 32 mg/m ³ Industry - Dermal; Long term systemic effects: 25 mg/kg/day Industry - Inhalation; Long term systemic effects: 150 mg/m ³
PNEC	No PNEC available. Substance is a hydrocarbon UVCB. Standard tests for this endpoint are intended for single substances and are not appropriate for the risk assessment of this complex substance.
8.2. Exposure controls	
Protective equipment	
Appropriate engineering controls	Provide adequate ventilation. Good general ventilation should be adequate to control worker exposure to airborne contaminants.
Eye/face protection	Chemical splash goggles.
Hand protection	To protect hands from chemicals, gloves should comply with European Standards EN388 and 374. As a general principle, exposure should be managed by means other than the provision of protective gloves. It is recommended that gloves are made of the following material: Polyvinyl alcohol (PVA). Thickness: 0.2 - 0.3 mm or Polyethylene. Thickness: > 0.062 mm Permeation breakthrough time according to EN374 - class: (1-6) e.g. minimum 480 mins. Caution: The performance of gloves under actual working conditions can be significantly affected by many factors and the information provided according to EN374 may not accord with what is achieved in practice. We recommend that expert professional advice is sought that takes into account of the work processes and working environment applicable for each task where gloves are to be worn.
Other skin and body protection	Wear suitable protective clothing as protection against splashing or contamination.
Hygiene measures	Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly with soap and water if skin becomes contaminated. Do not smoke in work area.
Respiratory protection	In case of inadequate ventilation or risk of inhalation of vapours, use suitable respiratory equipment with combination filter (type A2/P3).

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Clear liquid.
Colour	Colourless.
Odour	Organic solvents.
Odour threshold	Not available.
рН	Not applicable.
Melting point	Not applicable.
Initial boiling point and range	140 - 200°C @ 760 mm Hg
Flash point	43°C Closed cup.
Evaporation rate	0.16 (butyl acetate = 1)

Upper/lower flammability or explosive limits	Lower flammable/explosive limit: 0.7 g/100 g Upper flammable/explosive limit: 7.0 g/100 g	
Vapour pressure	0.29 kPa @ °C	
Vapour density	~ 4.2	
Relative density	0.882 @ 15°C	
Bulk density	882 kg/m ³	
Solubility(ies)	Immiscible with water Miscible with the following materials: Organic solvents.	
Auto-ignition temperature	450°C	
Viscosity	<30 seconds 3mm ISO cup s @ 25°C	
9.2. Other information		
Molecular weight	122	
Volatility	100 Scientifically unjustified.	
Volatile organic compound	This product contains a maximum VOC content of 880 g/litre.	
SECTION 10: Stability and read	· · ·	
10.1. Reactivity	Survey Sarvey	
Reactivity	See the other subsections of this section for further details.	
10.2. Chemical stability		
Stability	Stable at normal ambient temperatures and when used as recommended. Stable under the prescribed storage conditions.	
10.3. Possibility of hazardous r	eactions	
Possibility of hazardous reactions	No potentially hazardous reactions known.	
10.4. Conditions to avoid		
Conditions to avoid	Avoid heat. Containers can burst violently or explode when heated, due to excessive pressure build-up.	
10.5. Incompatible materials		
Materials to avoid	No specific material or group of materials is likely to react with the product to produce a hazardous situation.	
10.6. Hazardous decomposition products		
Hazardous decomposition products	Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Harmful gases or vapours.	
SECTION 11: Toxicological information		
11.1. Information on toxicologic	cal effects	
Toxicological effects	Not regarded as a health hazard under current legislation.	
Acute toxicity - oral Notes (oral LD₅₀)	Based on available data the classification criteria are not met.	
Acute toxicity - dermal Notes (dermal LD₅₀)	Based on available data the classification criteria are not met.	

Acute toxicity - inhalation Notes (inhalation LC_{50})	Based on available data the classification criteria are not met.
Skin corrosion/irritation Animal data	Based on available data the classification criteria are not met.
Serious eye damage/irritation Serious eye damage/irritation	Based on available data the classification criteria are not met.
Respiratory sensitisation Respiratory sensitisation	Based on available data the classification criteria are not met.
Skin sensitisation Skin sensitisation	Based on available data the classification criteria are not met.
Germ cell mutagenicity Genotoxicity - in vitro	Based on available data the classification criteria are not met.
Carcinogenicity Carcinogenicity	Based on available data the classification criteria are not met.
IARC carcinogenicity	None of the ingredients are listed or exempt.
Reproductive toxicity Reproductive toxicity - fertility	Based on available data the classification criteria are not met.
Reproductive toxicity - development	Based on available data the classification criteria are not met.
Specific target organ toxicity - STOT - single exposure	<u>single exposure</u> STOT SE 3 - H335, H336 May cause respiratory irritation. May cause drowsiness or
	dizziness.
Target organs	dizziness. Respiratory system, lungs Central nervous system
Target organs Specific target organ toxicity -	Respiratory system, lungs Central nervous system
	Respiratory system, lungs Central nervous system
Specific target organ toxicity -	Respiratory system, lungs Central nervous system repeated exposure
Specific target organ toxicity - STOT - repeated exposure Aspiration hazard	Respiratory system, lungs Central nervous system repeated exposure Not classified as a specific target organ toxicant after repeated exposure. Asp. Tox. 1 - H304 May be fatal if swallowed and enters airways. Pneumonia may be the
Specific target organ toxicity - STOT - repeated exposure Aspiration hazard Aspiration hazard	Respiratory system, lungs Central nervous system repeated exposure Not classified as a specific target organ toxicant after repeated exposure. Asp. Tox. 1 - H304 May be fatal if swallowed and enters airways. Pneumonia may be the result if vomited material containing solvents reaches the lungs. The severity of the symptoms described will vary dependent on the concentration and the
Specific target organ toxicity - STOT - repeated exposure Aspiration hazard Aspiration hazard	Respiratory system, lungs Central nervous system repeated exposure Not classified as a specific target organ toxicant after repeated exposure. Asp. Tox. 1 - H304 May be fatal if swallowed and enters airways. Pneumonia may be the result if vomited material containing solvents reaches the lungs. The severity of the symptoms described will vary dependent on the concentration and the length of exposure. A single exposure may cause the following adverse effects: Irritation of nose, throat and airway. Difficulty in breathing. Coughing. Vapours may cause headache, fatigue, dizziness and nausea. Central nervous system depression. During application and drying, solvent
Specific target organ toxicity - STOT - repeated exposure Aspiration hazard Aspiration hazard General information Inhalation	Respiratory system, lungs Central nervous system repeated exposure Not classified as a specific target organ toxicant after repeated exposure. Asp. Tox. 1 - H304 May be fatal if swallowed and enters airways. Pneumonia may be the result if vomited material containing solvents reaches the lungs. The severity of the symptoms described will vary dependent on the concentration and the length of exposure. A single exposure may cause the following adverse effects: Irritation of nose, throat and airway. Difficulty in breathing. Coughing. Vapours may cause headache, fatigue, dizziness and nausea. Central nervous system depression. During application and drying, solvent vapours will be emitted. Vapours in high concentrations are narcotic. Gastrointestinal symptoms, including upset stomach. Fumes from the stomach contents may be inhaled, resulting in the same symptoms as inhalation. Aspiration hazard if swallowed.
Specific target organ toxicity - STOT - repeated exposure Aspiration hazard Aspiration hazard General information Inhalation	Respiratory system, lungs Central nervous system repeated exposure Not classified as a specific target organ toxicant after repeated exposure. Asp. Tox. 1 - H304 May be fatal if swallowed and enters airways. Pneumonia may be the result if vomited material containing solvents reaches the lungs. The severity of the symptoms described will vary dependent on the concentration and the length of exposure. A single exposure may cause the following adverse effects: Irritation of nose, throat and airway. Difficulty in breathing. Coughing. Vapours may cause headache, fatigue, dizziness and nausea. Central nervous system depression. During application and drying, solvent vapours will be emitted. Vapours in high concentrations are narcotic. Gastrointestinal symptoms, including upset stomach. Furmes from the stomach contents may be inhaled, resulting in the same symptoms as inhalation. Aspiration hazard if swallowed. Entry into the lungs following ingestion or vomiting may cause chemical pneumonitis.

Target organs

Central nervous system Respiratory system, lungs

Toxicological information on ingredients.

Acute toxicity - oral	
Acute toxicity oral (LD₅₀ mg/kg)	3,492.0
Species	Rat
Notes (oral LD∞)	Based on available data the classification criteria are not met.
ATE oral (mg/kg)	3,492.0
Acute toxicity - dermal	
Acute toxicity dermal (LD₅₀ mg/kg)	3,160.0
Species	Rabbit
Notes (dermal LD₅₀)	Based on available data the classification criteria are not met.
ATE dermal (mg/kg)	3,160.0
Acute toxicity - inhalation	
Acute toxicity inhalation (LC∞ vapours mg/l)	6,193.0
Species	Rat
Notes (inhalation LC₅₀)	Based on available data the classification criteria are not met.
ATE inhalation (vapours mg/l)	6,193.0
Skin corrosion/irritation	
Animal data	Repeated exposure may cause skin dryness or cracking.
Serious eye damage/irritati	on
Serious eye damage/irritation	Based on available data the classification criteria are not met.
Respiratory sensitisation	
Respiratory sensitisation	Based on available data the classification criteria are not met.
Skin sensitisation	
Skin sensitisation	Based on available data the classification criteria are not met.
Germ cell mutagenicity	
Genotoxicity - in vitro	Based on available data the classification criteria are not met.
Carcinogenicity	
Carcinogenicity	Based on available data the classification criteria are not met.
IARC carcinogenicity	None of the ingredients are listed or exempt.
Reproductive toxicity	

Reproductive toxicity - fertility	Based on available data the classification criteria are not met.
Reproductive toxicity - development	Based on available data the classification criteria are not met.
Specific target organ toxicit	y - single exposure
STOT - single exposure	STOT SE 3 - H335, H336 May cause respiratory irritation. May cause drowsiness or dizziness.
Target organs	Respiratory system, lungs Central nervous system
Specific target organ toxicit	y - repeated exposure
STOT - repeated exposure	Not classified as a specific target organ toxicant after repeated exposure.
Aspiration hazard	
Aspiration hazard	Asp. Tox. 1 - H304 May be fatal if swallowed and enters airways. Pneumonia may be the result if vomited material containing solvents reaches the lungs.
General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Inhalation	A single exposure may cause the following adverse effects: Irritation of nose, throat and airway. Difficulty in breathing. Coughing. Vapours may cause headache, fatigue, dizziness and nausea. Central nervous system depression. During application and drying, solvent vapours will be emitted. Vapours in high concentrations are narcotic.
Ingestion	Gastrointestinal symptoms, including upset stomach. Fumes from the stomach contents may be inhaled, resulting in the same symptoms as inhalation. Aspiration hazard if swallowed. Entry into the lungs following ingestion or vomiting may cause chemical pneumonitis.
Skin contact	Repeated exposure may cause skin dryness or cracking. Discoloration of the skin.
Eye contact	May cause temporary eye irritation.
Route of exposure	Ingestion Inhalation Skin and/or eye contact
Target organs	Central nervous system Respiratory system, lungs

SECTION 12: Ecological information

Ecotoxicity

Dangerous for the environment: May cause long-term adverse effects in the aquatic environment.

12.1. Toxicity

Toxicity

Based on available data the classification criteria are not met.

Ecological information on ingredients.

Toxicity	Aquatic Chronic 2 - H411 Toxic to aquatic life with long lasting effects.
Acute aquatic toxicity	
Acute toxicity - fish	LC_{50} , 96 hours: 9.2 mg/l, Oncorhynchus mykiss (Rainbow trout)

	Acute toxicity - aquatic invertebrates	EC₅₀, 48 hours: 3.2 mg/l, Daphnia magna
	Acute toxicity - microorganisms	EC₅₀, 48 hours: 2.9 mg/l,
	Chronic aquatic toxicity	
	Chronic toxicity - fish early life stage	NOEC, 28 days: 1.23 mg/l, Oncorhynchus mykiss (Rainbow trout)
	Chronic toxicity - aquatic invertebrates	NOEC, 21 : 2.14 mg/l, Daphnia magna
12.2. Persis	stence and degradability	
Persistence	and degradability The deg	radability of the product is not known.
Ecological i	nformation on ingredients.	
		HYDROCARBONS, C9, AROMATICS
	Persistence and degradability	The degradability of the product is not known.
	Biodegradation	- 78%: 28 days
12.3. Bioac	cumulative potential	
Bioaccumu	lative potential No data	available on bioaccumulation.
Ecological i	nformation on ingredients.	
		HYDROCARBONS, C9, AROMATICS
	Bioaccumulative potential	No data available on bioaccumulation.
	Partition coefficient	Not available.
12.4. Mobili	ity in soil	
Mobility	No data	available.
Ecological i	nformation on ingredients.	
		HYDROCARBONS, C9, AROMATICS
	Mobility	No data available
12.5 Dooul	Mobility	No data available.
	ts of PBT and vPvB assessm	nent
	ts of PBT and vPvB assessm PBT and vPvB This sub	
Results of F assessmen	ts of PBT and vPvB assessm PBT and vPvB This sub	nent
Results of F assessmen	ts of PBT and vPvB assessm PBT and vPvB This sub t	nent
Results of F assessmen	ts of PBT and vPvB assessm PBT and vPvB This sub t	nent stance is not classified as PBT or vPvB according to current EU criteria. <u>HYDROCARBONS, C9, AROMATICS</u>
Results of F assessmen Ecological i	ts of PBT and vPvB assessm PBT and vPvB This sub t Information on ingredients. Results of PBT and vPvB	nent stance is not classified as PBT or vPvB according to current EU criteria. <u>HYDROCARBONS, C9, AROMATICS</u>
Results of F assessmen Ecological i	ts of PBT and vPvB assessm PBT and vPvB This sub t information on ingredients. Results of PBT and vPvB assessment adverse effects	nent stance is not classified as PBT or vPvB according to current EU criteria. <u>HYDROCARBONS, C9, AROMATICS</u> This substance is not classified as PBT or vPvB according to current EU criteria.
Results of F assessmen Ecological i 12.6. Other Other adver	ts of PBT and vPvB assessm PBT and vPvB This sub t information on ingredients. Results of PBT and vPvB assessment adverse effects	nent stance is not classified as PBT or vPvB according to current EU criteria. <u>HYDROCARBONS, C9, AROMATICS</u> This substance is not classified as PBT or vPvB according to current EU criteria.

Other adverse eff	ects None known.	
SECTION 13: Disposal considerations		
13.1. Waste treatment method	<u>s</u>	
General information	The generation of waste should be minimised or avoided wherever possible. Reuse or recycle products wherever possible. This material and its container must be disposed of in a safe way. Disposal of this product, process solutions, residues and by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements.	
Disposal methods	Dispose of surplus products and those that cannot be recycled via a licensed waste disposal contractor. Waste packaging should be collected for reuse or recycling. Incineration or landfill should only be considered when recycling is not feasible. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of the local water authority.	
Waste class	When this coating, in its liquid state, as supplied, becomes a waste, it is categorised as hazardous waste, with code 08 01 11* (SOLVENT BASED LIQUID WASTE). Part-used containers, not drained and/or rigorously scraped out and containing dried residues of the supplied coating, are categorised as hazardous waste, with code 08 01 11* (SOLVENT BASED LIQUID WASTE). Used containers, drained and/or rigorously scraped out and containing dry residues of the supplied coating, are categorised coating, are categorised as non-hazardous waste, with code 15 01 02 (plastic packaging) or 15 01 04 (metal packaging).	
SECTION 14: Transport inform	nation	
General	For limited quantity packaging/limited load information, consult the relevant modal documentation using the data shown in this section.	
14.1. UN number		
UN No. (ADR/RID)	1263	
UN No. (IMDG)	1263	
UN No. (ICAO)	1263	
14.2. UN proper shipping name	9	
Proper shipping name (ADR/RID)	PAINT RELATED MATERIAL Contains HYDROCARBONS, C9, AROMATICS Class 3, PGIII, (f.p. 38 C), MARINE POLLUTANT	
Proper shipping name (IMDG)	PAINT RELATED MATERIAL Contains HYDROCARBONS, C9, AROMATICS Class 3, PGIII, (f.p. 38 C), MARINE POLLUTANT	
Proper shipping name (ICAO)	PAINT RELATED MATERIAL Contains HYDROCARBONS, C9, AROMATICS Class 3, PGIII, (f.p. 38 C), MARINE POLLUTANT	
14.3. Transport hazard class(e	<u>s)</u>	
ADR/RID class	3	
IMDG class	3	
ICAO class/division	3	

Transport labels



14.4. Packing group

ADR/RID packing group	III
IMDG packing group	III
ICAO packing group	III

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant



14.6. Special precautions for user

Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

EmS F-E, S-E

Tunnel restriction code (D/E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable. Annex II of MARPOL 73/78 and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended). Commission Regulation (EU) No 2015/830 of 28 May 2015. Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).
Guidance	Workplace Exposure Limits EH40.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Abbreviations and acronyms used in the safety data sheet	 ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road. ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways. RID: European Agreement concerning the International Carriage of Dangerous Goods by Rail. IATA: International Air Transport Association. ICAO: Technical Instructions for the Safe Transport of Dangerous Goods by Air. IMDG: International Maritime Dangerous Goods. CAS: Chemical Abstracts Service. ATE: Acute Toxicity Estimate. LCso: Lethal Concentration to 50 % of a test population. LDso: Lethal Dose to 50% of a test population (Median Lethal Dose). ECso: 50% of maximal Effective Concentration. PBT: Persistent, Bioaccumulative and Toxic substance. vPvB: Very Persistent and Very Bioaccumulative.
Classification abbreviations and acronyms	Acute Tox. = Acute toxicity Aquatic Acute = Hazardous to the aquatic environment (acute) Aquatic Chronic = Hazardous to the aquatic environment (chronic) Asp. Tox. = Aspiration hazard Eye Dam. = Serious eye damage Flam. Liq. = Flammable liquid STOT SE = Specific target organ toxicity-single exposure
Training advice	Read and follow manufacturer's recommendations. Only trained personnel should use this material.
Revision comments	Issued in new format for Reach compliance in accordance with EC 1272/2008 Issued in accordance with Annex II to REACH, as amended by Commission Regulation (EU) No. 2015/830
Issued by	Technical Dept. (N.O.)
Revision date	24/03/2021
Revision	FIRST ISSUE
SDS number	21113
SDS status	Approved.
Hazard statements in full	H226 Flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H411 Toxic to aquatic life with long lasting effects.
Signature	Initials

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.