

| Trade name : | Lacq Produra Black | | |
|-----------------|--------------------|-----------|-------|
| Revision date : | 27.03.2017 | Version : | 1.0.0 |
| Print date : | 30-03-2017 | | |

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Lacq Produra Black (6550)

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses

Product Categories [PC]

PC9A - Coatings and paints, thinners, paint removers

1.3 Details of the supplier of the safety data sheet Supplier (manufacturer/importer/only representative/downstream user/distributor) Vliegenthart B.V. Street : Zuiderhavenweg 42

Postal code/city: 4004 JJ TIEL

Telephone : +31 (0)344 63 33 36

Telefax : +31 (0)344 63 16 16

1.4 Emergency telephone number


+31 (0)344 63 33 36

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008 [CLP] Skin Sens. 1 ; H317 - Skin sensitisation : Category 1 ; May cause an allergic skin reaction.

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP] Hazard pictograms





| Trade name : Revision date : | Lacq Produra Black 27.03.2017 | Version : | 1.0.0 |
|---------------------------------|----------------------------------|-----------|-------|
| Print date : | 30-03-2017 | | |
| P102 | Keep out of reach of children. | | |
| D2C1 | | | |

| P261 | Avoid breathing dust/fume/gas/mist/vapours/spray. |
|-------------|--|
| P273 | Avoid release to the environment. |
| P280 | Wear protective gloves/protective clothing/eye protection/face protection. |
| P333+P313 | If skin irritation or rash occurs: Get medical advice/attention. |
| P302+P352 | IF ON SKIN: Wash with plenty of water/ |
| hay havanda | |

2.3 Other hazards

None

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous ingredients

3-IODO-2-PROPYNYL BUTYLCARBAMATE ; EC No. : 259-627-5; CAS No. : 55406-53-6

| Weight fraction : | ≥ 0,1 - < 1 % | | |
|---|---|--|--|
| Classification 1272/2008 [CLP] : | Acute Tox. 3 ; H331 STOT RE 1 ; H372 Eye Dam. 1 ; H318 Acute Tox. 4 ; H302 Skin Sens. 1 ; H317 Aquatic Acute 1 ; H400 Aquatic Chronic 1 ; H410 | | |
| A MIXTURE OF: 5-CHLORO-2-METHYL 55965-84-9 | -2H-ISOTHIAZOL-3-ONE AND 2- METHYL-2H-ISOTHIAZOL-3-ONE (3:1) ; CAS No. : | | |
| Weight fraction : | ≥ 0,0015 - < 0,06 % | | |
| Classification 1272/2008 [CLP] : | Acute Tox. 3 ; H301 Acute Tox. 3 ; H311 Acute Tox. 3 ; H331 Skin Corr. 1B ; H314 Eye Dam. 1 ; H318 Skin Sens. 1 ; H317 Aquatic Acute 1 ; H400 Aquatic Chronic 1 ; | | |

Additional information

Full text of H- and EUH-phrases: see section 16.

3.3 Additional information

All ingredients of this mixture are (pre)registered according to REACH regulation.

H410

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

When in doubt or if symptoms are observed, get medical advice. Never give anything by mouth to an unconscious person or a person with cramps.

Following inhalation

Remove casualty to fresh air and keep warm and at rest. If breathing is irregular or stopped, administer artificial respiration.

In case of skin contact

After contact with skin, wash immediately with plenty of water and soap. Do not wash with: Solvents/Thinner

After eye contact

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

After ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate



| Trade name : | Lacq Produra Black | | |
|-----------------|--------------------|-----------|-------|
| Revision date : | 27.03.2017 | Version : | 1.0.0 |
| Print date : | 30-03-2017 | | |

medical attention. Do NOT induce vomiting. Keep at rest.

- **4.2 Most important symptoms and effects, both acute and delayed** No information available.
- 4.3 Indication of any immediate medical attention and special treatment needed None

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

alcohol resistant foam Extinguishing powder Carbon dioxide (CO2) Sand Water mist

Unsuitable extinguishing media

High power water jet

5.2 Special hazards arising from the substance or mixture None

5.3 Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

5.4 Additional information Burning produces heavy smoke. Do not allow run-off from fire-fighting to enter drains or water courses. Use water spray jet to protect personnel and to cool endangered containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Provide adequate ventilation. Wear breathing apparatus if exposed to vapours/dusts/aerosols. See protective measures under point 7 and 8.

6.2 Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3 Methods and material for containment and cleaning up

For cleaning up

Treat the recovered material as prescribed in the section on waste disposal. Clean with detergents. Avoid solvent cleaners.

6.4 Reference to other sections

None

SECTION 7: Handling and storage

7.1 Precautions for safe handling



Trade name : Revision date : Print date : Lacq Produra Black 27.03.2017 30-03-2017

Version :

1.0.0



Protective measures

Only use the material in places where open light, fire and other flammable sources can be kept away. Wear personal protection equipment (refer to section 8). If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

Measures to prevent fire

Vapours are heavier than air, spread along floors and form explosive mixtures with air. Vapours can form explosive mixtures with air.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Ensure adequate ventilation of the storage area. Restrict access to stockrooms.

Hints on joint storage

Storage class : 12

Storage class (TRGS 510): 12

Keep away from

Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.

7.3 Specific end use(s)

None

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

None

8.2 Exposure controls

Appropriate engineering controls

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL (=Occupational Exposure Limit), suitable respiratory protection must be worn.

Personal protection equipment

Eye/face protection



Eye glasses with side protection

Skin protection

For the protection against direct skin contact, body protective clothing is essential (in addition to the usual working clothes).

Hand protection



CC

Trade name : Revision date : Print date : Lacq Produra Black 27.03.2017 30-03-2017

Version :

1.0.0



PVC (Polyvinyl chloride) PE (polyethylene) NR (natural rubber, natural latex) DIN EN 374 Thickness of the glove material => 0,4 mm Breakthrough time (maximum wearing time) > 30 min

Respiratory protection

Respiratory protection necessary at: exceeding exposure limit values If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Colour : black

Odour : characteristic

Safety relevant basis data

| | Physical state : Melting point/melting range : | | | liquid No data available | |
|-----|--|---------------|---------|--|-------------------|
| | Initial boiling point and boiling range : | (1013 hPa) | | Not determined | |
| | Decomposition temperature : Flash point : | (1013 hPa) | | Not determined Not determined | |
| | Ignition temperature : Lower explosion limit : Upper explosion limit : | | | Not determined Not determined Not determined | |
| | Vapour pressure : | (50 °C) | < | 1000 | hPa |
| | Density : | (20 °C) | approx. | 1,058 | g/cm ³ |
| | Water solubility : pH : log P O/W : | (20 °C) | | Not determined not applicable not determined | |
| | Viscosity : Odour threshold : Evaporation rate : | (20 °C) | | Not determined not determined not determined | |
| 9.2 | Oxidising liquids : Other information | Not relevant. | | | |
| 5.2 | | | | | |

None

SECTION 10: Stability and reactivity

10.1 Reactivity

No information available.

10.2 Chemical stability

No information available.

10.3 Possibility of hazardous reactions No information available.



 Trade name :
 Lacq Produra Black

 Revision date :
 27.03.2017
 Version :
 1.0.0

 Print date :
 30-03-2017
 Version :
 1.0.0

10.4 Conditions to avoid

No information available.

10.5 Incompatible materials No information available.

10.6 Hazardous decomposition products No information available.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

No information available.

11.5 Additional information

The statement is derived from the properties of the single components.

SECTION 12: Ecological information

12.1 Toxicity

No information available.

- **12.2 Persistence and degradability** No information available.
- **12.3 Bioaccumulative potential** No information available.
- **12.4 Mobility in soil** No information available.
- 12.5 Results of PBT and vPvB assessment No information available.
- **12.6 Other adverse effects** No information available.

12.7 Additional ecotoxicological information

Additional information

Product should not be released into water without pre-treatment (biological sewage plant).

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product/Packaging disposal

Waste treatment options

Appropriate disposal / Package

Contaminated packages must be completely emptied and can be re-used following proper cleaning. The generation of waste should always as far as possible be avoided, or be limited to a minimum. Disposal of this product, solutions and any by-products should at all times be in accordance with applicable legislation in the field of environmental protection and waste disposal legislation and any other regional or local regulations.



Trade name : Revision date : Print date : Lacq Produra Black 27.03.2017 30-03-2017

Version :

1.0.0

SECTION 14: Transport information

14.1 UN number

No dangerous goods in sense of this transport regulation.

14.2 UN proper shipping name

No dangerous goods in sense of this transport regulation.

14.3 Transport hazard class(es) No dangerous goods in sense of this transport regulation.

14.4 Packing group No dangerous goods in sense of this transport regulation.

14.5 Environmental hazards

No dangerous goods in sense of this transport regulation.

14.6 Special precautions for user

None

SECTION 15: Regulatory information

^{15.1} Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations Technische Anleitung Luft (TA-Luft) Weight fraction (Number 5.2.5. I) : < 5 % Water hazard class (WGK) Class : 2 (Hazardous to water) Classification according to VwVwS Other regulations, restrictions and prohibition regulations Betriebssicherheitsverordnung (BetrSichV) No flammable liquid according to BetrSichV.

15.2 Chemical safety assessment

No information available.

SECTION 16: Other information

16.1 Indication of changes

- None
- 16.2 Abbreviations and acronyms None
- 16.3 Key literature references and sources for data None
- ^{16.4} Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

No information available.

16.5 Relevant H- and EUH-phrases (Number and full text)



| Trade name : Revision date : Print date : | Lacq Produra Black 27.03.2017 30-03-2017 | Version : | 1.0.0 |
|---|--|-----------|-------|
| H301+H311+H331 H302 H314 H317 | Toxic if swallowed, in contact with skin or if inhaled. Harmful if swallowed. Causes severe skin burns and eye damage. May cause an allergic skin reaction. | | |

H318 Causes serious eye damage.

H331 Toxic if inhaled. H372 Causes damage

- Causes damage to organs through prolonged or repeated exposure.
- H410 Very toxic to aquatic life with long lasting effects.

16.6 Training advice

None

16.7 Additional information

None

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storag