



Lacq Decowax Technical Specifications

Lacq Decowax is a wax that can be used to maintain wooden surfaces. Decowax is manufactured using traditional methods based on a 60-year old, proven recipe. The interaction of pure turpentine, all natural beeswax and carnauba wax, create a natural shine, structure and colour perception. Decowax provides a protective layer and evens out minor irregularities. This makes this wax extremely well-suited for treating furniture and floors, or as a protective top layer over chalk paint.

Decowax cleans, protects and preserves wooden surfaces. Treatment with this wax provides a beautiful shine and removes superficial spots and scratches. Decowax can be used to temper bright colours, apply an antique or gray patina or create a whitewash effect. In addition, the wax can be used to give untreated wood a colour or unique effect. The Decowax metallic colours can be used to add exquisite sparkling effects to a wooden surface. The possibilities are endless.

Substrate

Decowax only adheres to a porous substrate, such as untreated wood or a porous paint layer, such as chalk paint. Before applying Decowax, a smooth layer of lacquer should be removed.

Wood is a natural product, results and colour perception may vary depending on the substrate.

Application

1: Apply Decowax using an brush, sponge or lint-free cloth. A brush can be handy for carved wood or relief surfaces.

2: Spread the wax evenly across the surface and after fifteen to thirty minutes wipe off the excess wax with a cloth, so that only a thin, even layer remains. This allows the wax to soak into the substrate.

3: Allow the remaining wax to soak in and harden overnight and then firmly polish the wax layer. By polishing it, the wax layer becomes smooth, strong and hard, and acquires a soft shine.

Finishing

A wax layer requires no further finishing. However, you will need to touch it up from time to time, and you need to continue to maintain it with wax. The wax layer can easily be touched up, in its entirety or locally.

Coverage

Depending on the substrate and the method of application, the coverage is approx 6 m² per can.

Safety precautions

- Read the safety sheet.
- Do not inhale Decowax vapors.
- Wear safety goggles and gloves
- If swallowed, consult a doctor and bring the safety sheet.

Normal colors: Antique Brown, Chalky Grey, Chalky White, Taupe, Anthracite, Nordic Blue, Antique Green, Antique Pink, Clear

Metallic colors: Gold Metallic, Copper Metallic, Bronze Metallic

Packaging: Tin can 370 ML

The information in this data sheet is given to the best of our knowledge based on laboratory tests & practical information, however as the product is often used under condition beyond our control, we cannot guarantee anything but the quality of the product itself.

We reserve the right to change the data supplied without notice.